



BASE ME



| SYMBOL | DIMENSIONS IN MILLIMETERS | | |
|--------|---------------------------|-------|------|
| | MIN | NOM | MAX |
| A | — | — | 1.75 |
| A1 | 0.10 | 0.15 | 0.25 |
| A2 | 1.30 | 1.40 | 1.50 |
| A3 | 0.60 | 0.65 | 0.70 |
| b | 0.23 | — | 0.31 |
| b1 | 0.22 | 0.25 | 0.28 |
| c | 0.20 | — | 0.24 |
| c1 | 0.19 | 0.20 | 0.21 |
| D | 8.55 | 8.65 | 8.75 |
| E | 5.80 | 6.00 | 6.20 |
| E1 | 3.80 | 3.90 | 4.00 |
| e | — | 0.635 | BSC |
| h | 0.30 | — | 0.50 |
| L | 0.50 | — | 0.80 |
| L1 | — | 1.05 | REF |
| theta | 0 | — | 8° |



正不
式准
文复
件印
16年6月13日

| REV. | Description | Signature |
|--------------|-------------|-----------|
| Drafted By | | Verified |
| Confirmed By | Xiang | Verified |
| Verified By | | Approved |

| | |
|---------------------------------------|-------------------------------|
| Tianshui Huatong Technology Co., Ltd. | |
| Title | Standard |
| Part No. | SOP20L (0.635-D1.40) P00D(8R) |
| DWG No. | TFP0200308-8P |
| Rev. | REV. A |
| Effective Date | 2016/05/27 |